

HAFFMANS

O₂ GEHALTEMETER, TYPE o-DGM

OPTICAL O₂ MEASUREMENT

The Pentair Haffmans O₂ Gehaltemeter, type o-DGM offers high accuracy and portable measurement of O₂, significantly improving response times compared to traditional O₂ measuring devices. With no frequent calibration needed, it provides brewers with a reliable, low-maintenance solution for optimizing their brewing process.

The o-DGM is available in two measuring ranges:

- Low measuring range (LHO) for accurate DO measurement of beverages < 2,000 ppb (e.g. beer and deaerated water)
- Wide measuring range (WLO) for accurate DO measurement of beverages < 45 mg/l (e.g. wort, soft drinks and non-deaerated water)

Three measurement modes are available, single sample, continuous O₂ measurement from the production process and TPO measurement, based on the Uhlig method, from a package.

The data can be securely transferred to a PC by using the interface cable. Data analysis can be done via Pentair Haffmans Navigator software.



CUSTOMER BENEFITS

- **Portable measurement allows for easy quality control, helping to reduce product losses**
- **Optical-based technology for high accuracy**
- **Easy to maintain**
- **Ability to measure the purity of CO₂ gas**

APPLICATIONS

- **At-line, sampled directly during the production process**
- **Laboratory, after the filling sampling from bottles or cans by using the sampling device Pentair Haffmans ISD 2.0**
- **TPO calculation from bottles or cans using the sampling device Pentair Haffmans ISD 2.0**

HAFFMANS

O₂ GEHALTEMETER, TYPE o-DGM

TECHNICAL DATA

O₂ Sensor LHO

Measuring Range 0.0 to 2,000 ppb w/w (DO)
0 to 41,800 ppm vol/vol (gas)
Accuracy ± 1 ppb w/w + 2 % of m.v. (DO)*
 $\pm (20 \text{ ppm vol/vol} + 2\% \text{ of the m.v. (gas)})^*$

O₂ Sensor WLO

Measuring Range 0 to 45,000 ppb w/w (DO)
0 to 1,000,000 ppm vol/vol (gas)
Accuracy < 5% of m.v. from 100 ppb (DO)*
< 5% of m.v. from 2,300 ppm (gas)*

Measuring Units

ppb w/w, µg/l, ppm w/w, mg/l, % a.s., % O₂, ppm vol/vol

Temperature

-5.0 - 40.0 °C, acc. ± 0.2 °C

Memory Capacity

Up to 400 measurements

Voltage

80-240 V / AC 50-60 Hz

Interface

RS-232

Dimensions

210 x 130 x 200 (LxWxH mm)

Weight

ca. 2.4 kg

* at 20 °C

SCOPE OF SUPPLY

- O₂ Gehaltemeter, type o-DGM
- Bumper
- Service set with power supply (Euro or US plug)
- Software set (USB stick with Navigator software & interface cable to connect RS232 to USB)
- Set of two sample hoses
- Instruction manual

OPTIONS

- Certificate of measurement
- Quick charger
- Sampling device Pentair Haffmans ISD 2.0



HAFFMANS B.V.

P.O. BOX 3150, 5902 RD VENLO, NETHERLANDS FOODANDBEVERAGE.PENTAIR.COM

All Pentair trademarks and logos are owned by Pentair. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

haffmans-o-dgm-gehaltemeter-2539-en ©2025 Pentair, All Rights Reserved.

